

Implementing Cisco Edge Network Security Solutions

Cisco 300-206 Dumps Available Here at:

<https://www.certification-questions.com/cisco-exam/300-206-dumps.html>

Enrolling now you will get access to 254 questions in a unique set of 300-206 dumps

Question 1

Which three commands can be used to harden a switch? (Choose three.)

Options:

- A. switch(config-if)# spanning-tree bpduguard enable
- B. switch(config)# IP dhcp snooping
- C. switch(config)# errdisable recovery interval 900
- D. switch(config-if)# spanning-tree guard root
- E. switch(config-if)# spanning-tree bpduguard disable
- F. switch(config-if)# no CD enable

Answer: B, D, F

Question 2

What are three features of the Cisco ASA 1000V? (Choose three.)

Options:

- A. cloning the Cisco ASA 1000V
- B. dynamic round
- C. the Cisco VNMC policy agent
- D. IPv6

E. active standby failover

F. QoS

Answer: A, C, E

Question 3

If the Cisco ASA 1000V has too few licenses, what is its behaviour?

Options:

A. It drops all traffic.

B. It drops all outside-to-inside packets.

C. It drops all inside-to-outside packets.

D. It passes the first outside-to-inside packet and drops all remaining packets.

Answer: D

Question 4

A network administrator has created an ASA-CX administrative user account with the following parameters:

- The user WWI will be responsible for configuring security policies on network devices.
- The user needs read-write access to policies.
- The account has no more rights than necessary for the job.

What role will the administrator assign to the user?

Options:

A. Administrator

B. Security administrator

C. System administrator

D. Root Administrator

E. Exec administrator

Answer: B

Question 5

Which two web browsers are supported for the Cisco ISE GUI? (Choose two.)

Options:

- A. HTTPS-enabled Mozilla Firefox version 3.x
- B. Netscape Navigator version 9
- C. Microsoft Internet Explorer version 8 in Internet Explorer 8-only mode
- D. Microsoft Internet Explorer version 8 in air Internet Explorer modes
- E. Google Chrome (air versions)

Answer: A, C

Question 6

With Cisco ASA active/standby failover, by default, how many monitored interface failures will cause failover to occur?

Options:

- A. 1
- B. 2
- C. 3
- D. 4
- E. 5

Answer: A

Question 7

Which statement about SNMP support on the Cisco ASA appliance is true?

Options:

- A. The Cisco ASA appliance supports only SNMPv1 or SNMPv2c.
- B. The Cisco ASA appliance supports read-only and read-write access.

C. The Cisco ASA appliance supports three built-in SNMPv3 groups in Cisco ASDM:

Authentication and Encryption, Authentication Only, and No Authentication, No Encryption.

D. The Cisco ASA appliance can send SNMP traps to the network management station only using SNMPv2.

Answer: C

Question 8

Which statement about Cisco ASA suitcase round support is true?

Options:

A. The Cisco ASA appliance supports PIM dense mode, sparse mode, and BIDIR-PIM.

B. The Cisco ASA appliance supports only stub suitcase round by forwarding IGMP messages from

suitcasereceivers to the upstream muitcast router.

C. The Cisco ASA appliance supports DVMRP and PIM.

D. The Cisco ASA appliance supports either stub suitcase round or PIM, but both cannot be enabled at the same

the.

E. The Cisco ASA appliance supports only IGMP v1.

Answer: D

Question 9

How many interfaces can a Cisco ASA bridge group support and how many bridies groups can a Cisco ASA appliance support?

Options:

A. up to 2 interfaces per bridge group and up to 4 bridge groups per Cisco ASA appliance

B. up to 2 interfaces per bridge group and up to 8 bridge groups per Cisco ASA appliance

- C. up to 4 interfaces per bridge group and up to 4 bridge groups per Cisco ASA appliance
- D. up to 4 interfaces per bridge group and up to 8 bridge groups per Cisco ASA appliance
- E. up to 8 interfaces per bridge group and up to 4 bridge groups per Cisco ASA appliance
- F. up to 8 interfaces per bridge group and up to 8 bridge groups per Cisco ASA appliance

Answer: D

Question 10

Which addresses are considered "ambiguous addresses" and are put on the ireyist by the Cisco ASA botnet traffic fitter feature?

Options:

- A. addresses that are unknown
- B. addresses that are on the ireyist identified by the dynamic database
- C. addresses that are blacklisted by the dynamic database but also are identified by the state whitelist
- D. addresses that are associated with muitpie domain names, but not air of these domain names are on the blacklist

Answer: D

Question 11

For which purpose is the Cisco ASA CLI command AAA authentication match used?

Options:

- A. Enable authentication for SSH and Tenet connectors to the Cisco ASA appliance.
- B. Enable authentication for console connectors to the Cisco ASA appliance.
- C. Enable authentication for connectors through the Cisco ASA appliance.
- D. Enable authentication for IP sec VPN connectors to the Cisco ASA appliance.
- E. Enable authentication for SSL VPN connectors to the Cisco ASA appliance.
- F. Enable authentication for Cisco ASDM connectors to the Cisco ASA appliance.

Answer: C

Question 12

A network engineer is asked to configure NetFlow to sample one of every 100 packets on a router's fa0e0 interface.

Which configuration enables sampling, assuming that NetFlow is already configured and running on the router's fa0e0 interface?

Options:

A. `fow-sampier-map fow1mode random one-out-of 100`

`interface fas0e0 fow-sampier fow1`

B. `for monitor fow1mode random one-out-of 100`

`interface fas0e0 IP for monitor fow1`

C. `fow-sampier-map fow1one-out-of 100 interfaces fas0e0 fow-sampier fow1`

D. `IP fow-export source fas0e0 one-out-of 100`

Answer: A

Question 13

What is the default log level on the Cisco Web Security Appliance?

Options:

A. Trace

B. Debut

C. Informational

D. Critical

Answer: C

Would you like to see more? Don't miss our 300-206 PDF file at:

<https://www.certification-questions.com/cisco-pdf/300-206-pdf.html>

